

ADC-T3000

SPECIFICATIONS

POWER

2 AAA Batteries or 24 V power

DIMENSIONS

4.1 x 5 x 0.7" (10.4 x 12.6 x 1.8 cm)

OPERATING TEMPERATURE RANGE

32 to 120°F (0°C to 49°C)

COMMUNICATION

Z-Wave Plus

COMPATIBLE SYSTEMS

HUMIDIFIER

Yes

DEHUMIDIFIER

Yes

HEAT (FOSSIL OR ELECTRIC)

Up to 3 stages

COOL

Up to 2 stages

HEAT PUMP WITH AUX

Up to 5 stages

AUX HEAT

Up to 3 stages

DUAL FUEL (FOSSIL AUX HEAT)

Yes

FORCED AIR ZONED HEAT

Up to 3 stages

FORCED AIR ZONED COOL

Up to 2 stages

VENTILATION CONTROL

HRV, ERV, external air baffle



Smart Thermostat

Our award-winning, ENERGY STAR® certified Smart Thermostat has been updated by our in-house Design Studio to deliver the best in both form and function. With a rich OLED display, advanced diagnostics, and one-touch commands, Alarm.com's most innovative thermostat yet combines even smarter features with a superior design for maximum comfort. Enjoy precision comfort when paired with an Alarm.com Temperature Sensor.

INCLUDED IN THE BOX

- Thermostat
- User guide
- Batteries (x2 AAA)
- Drywall anchors and screws (x2)
- Wire labels

FEATURES

- Self-configuration for easier installation
- Flexible, easy-to-use controls
- Proactive detection of common system problems
- Humidity control

EASY INSTALLATION

Auto-detects wiring to simplify system configuration, eliminating errors and speeding up installations.

BROAD HVAC COMPATIBILITY

Works with virtually any conventional 24 V system. Supports multi-staged systems and heat pumps, zoned systems in which each zone has its own thermostat, humidifiers/dehumidifiers, and ventilation systems (HRV, VRV, external air baffle).

FLEXIBLE POWER OPTIONS

Improved push-button terminals and a more open backplate design make it easy to connect and disconnect wires without additional equipment. The new thermostat also has a 30% slimmer profile and a rich OLED display.

CUTTING EDGE SECURITY

Supports the latest in Z-Wave security using the S2 security protocol.